

Package: arena2r (via r-universe)

September 2, 2024

Type Package

Title Plots, Summary Statistics and Tools for Arena Simulation Users

Version 1.0.0

Author Pedro Nascimento de Lima [aut, cre]

Maintainer Pedro Nascimento de Lima <pedrolima.n@gmail.com>

Description Reads Arena <<https://www.arenasimulation.com/>> CSV output files and generates nice tables and plots. The package contains a 'Shiny' App that can be used to interactively visualize Arena's results.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports stats, utils, rlang, tidyr, magrittr, dplyr, purrr, shiny, shinydashboard, shinyBS, shinyjs, ggplot2

Depends R (>= 2.10)

Suggests testthat, covr, knitr, rmarkdown

RoxygenNote 6.1.0

URL <https://github.com/pedroliman/arena2r>

BugReports <https://github.com/pedroliman/arena2r/issues>

VignetteBuilder knitr

Repository <https://pedroliman.r-universe.dev>

RemoteUrl <https://github.com/pedroliman/arena2r>

RemoteRef HEAD

RemoteSha 53fb393e1ec13807f457f3d40e6304f45b308789

Contents

arena_results	2
get_simulation_results	2
get_statistics_summary	3
plot_box	4
plot_confint	4
plot_scatter	5
runArenaApp	5

Index	6
--------------	----------

arena_results	<i>Test Dataset with Arena Results</i>
---------------	----------------------------------------

Description

A dataset containing test data from an Arena simulation model

Usage

arena_results

Format

A data frame with 2280 rows and 4 variables:

Scenario The Scenario Name

Statistic The Statistic's description

Replication The Replication Number

Value The numeric value of the statistic within the replication and scenario

get_simulation_results	<i>Get Results from Arena CSV Files</i>
------------------------	-----------------------------------------

Description

This function reads all csv files inside the provided path and returns a data.frame with the simulation runs, consolidated. You should provide a path containing only csv files generated by Arena, with the same number of replications. I Suggest you to name your csv files after your scenarios.

Usage

```
get_simulation_results(source, source_type = "path")
```

Arguments

source	The path where csv files is stored, or a list coming from shiny. If you do not provide a value, I'll assume they're on your current working directory.
source_type	String that describes where the data is coming from. "path" stands for a path that contains all csv files. "shinyInput" stands for the list object returned by fileInput in the ShinyApp.

Value

a tidy dataframe with simulation results.

Examples

```
# Define de path where your csv files are:
path <- system.file("extdata", package = "arena2r")
simulation_results = get_simulation_results(path)
head(simulation_results)
```

get_statistics_summary

Get Statistics Summary

Description

Makes a summary table to every statistic available

Usage

```
get_statistics_summary(sim_results, confidence = 0.95)
```

Arguments

sim_results	The data.frame generated by get_simulation_results()
confidence	The confidence of the CI

Value

a data.frame with a summary for every Statistic

Examples

```
library(arena2r)

statistics_summary = get_statistics_summary(arena_results)
head(statistics_summary)
```

plot_box	<i>Box Plot</i>
----------	-----------------

Description

Plots a box plot for a response variable, across different simulated scenarios.

Usage

```
plot_box(sim_results, response_variable)
```

Arguments

`sim_results` The data.frame generated by `get_simulation_results()`
`response_variable` A character string indicating the Statistic to be plotted.

Value

a box plot using ggplot2.

Examples

```
library(arena2r)  
plot_box(arena_results, "Entity 1.NumberOut")
```

plot_confint	<i>Confidence Interval Plot</i>
--------------	---------------------------------

Description

Plots the confidence interval for a response variable, across different simulated scenarios.

Usage

```
plot_confint(sim_results, response_variable)
```

Arguments

`sim_results` The data.frame generated by `get_simulation_results()`
`response_variable` A character string indicating the Statistic to be plotted.

Value

a confidence interval plot using ggplot2.

Examples

```
library(arena2r)

plot_confint(arena_results, "Entity 1.WaitTime")
```

plot_scatter	<i>Scatter Plot</i>
--------------	---------------------

Description

Scatter Plot

Usage

```
plot_scatter(sim_results, x_variable, y_variable)
```

Arguments

sim_results	The data.frame generated by get_simulation_results()
x_variable	The name of the Statistic to be placed on the x axis
y_variable	The name of the Statistic to be placed on the y axis

Value

a scatter plot showing individual replication results

Examples

```
library(arena2r)

plot_scatter(arena_results, "Entity 1.NumberOut", "Entity 1.WaitTime")
```

runArenaApp	<i>Run Arena App</i>
-------------	----------------------

Description

This function will launch a Shiny App allowing you to analyse Arena results without writing R code.

Usage

```
runArenaApp()
```

Index

* datasets

arena_results, [2](#)

arena_results, [2](#)

get_simulation_results, [2](#)

get_statistics_summary, [3](#)

plot_box, [4](#)

plot_confint, [4](#)

plot_scatter, [5](#)

runArenaApp, [5](#)